



2" - 24"

# J & S Valve®

*2" - 24" Commercial Butterfly Valves*

## Specification Commercial Butterfly Valve

General Purpose Commercial Butterfly Valves shall be of the Wafer Body Style to fit between ANSI Class 125 or Class 250 Flanges. Lug Body Style is for dead end service and is available in ANSI Class 125 or Class 250 Flanges. Valve Body and shall be cast grey iron ASTM 126 Grade B. Valve stem shall be 304 stainless steel. The disc material shall be 316 stainless steel. The seat material shall be EPDM. The stem seals shall be o-rings made of EPDM. Valves 2" - 8" shall be lever operated and vales 10" and larger shall be gear operated unless automatic operation is specified. Valves shall be suitable for air service for temperature up to 250°F. Wafer Body Butterfly Series 2300 and Lug Body Butterfly Series 2500 shall be manufactured by J&S Valve and Manufacturing, Huffman, Texas, or engineer pre-approved equal

**Ph: (281) 324-3990** ▪ **Fax: (281) 324-4595**  
**2323 1<sup>st</sup> Street** ▪ **Huffman, TX 77336**  
**[JandSValve.com](http://JandSValve.com)** ▪ **[sales@JandSValve.com](mailto:sales@JandSValve.com)**