AWWA BUTTERFLY VALVE SEAT ON BODY

2800SB & 2900SB SIZES: 3" - 24"

1.00



- -

AWWA C504 BUTTERFLY VALVE SERIES 2800SB & 2900SB

FEATURES


- Meet and Exceed the Requirements of AWWA C504.
- Rubber Seats Vulcanized to the Body.
- Robust Design for Longer Service.
- Mounting Flange in Accordance with MSS SP-102 .
- Flange and Drilling Comply with ASME B16.1 Class 125 or Class 250.
- Mechanical-Joint Ends Comply with ANSI/AWWA C111/A21.11.
- Rated Working Pressure 150psi or 250psi.


CORROSION PROTECTION

• Coatings - Interior and Exterior: Fusion Bond in Compliance with AWWA C550.



PART NAME	MATERIALS	SPECIFICATION			
Body	Ductile Iron	A536 65-45-12			
Body Seat	Rubber	EPDM			
Disc	Ductile Iron with 316SS Seat				
Stem	Stainless Steel	TYPE 304			
O-Ring	Rubber	EPDM or Buna			
Sealing Bushing	Stainless Steel	TYPE 304			
Shaft Bushing	Brass	B16 C37700			
Bottom Plate	Ductile Iron	A536 65-45-12			





FLANGED ENDS 2800SB MJ ENDS 2900SB

DIMENSIONS

SIZI	E	3"	4"	6"	8"	10"	12"	14"	16"	18"	20"	24"
А		63/8"	7"	83/8"	9 5/8"	10 ^{3/4} "	121/2"	14"	16"	17 3/8"	181/2"	22 ^{1/2} "
С		2 1/8"	2 1/8"	2 1/8"	2 1/8"	2 1/8"	3 1/8"	3 1/8"	3 7/8"	3 7/8"	3 7/8"	3 7/8"
TOP FLA	TOP FLANGE		F07	F10	F10	F10	F12	F12	F16	F16	F16	F16
D	D		31/2"	47/8"	47/8"	47/8"	57/8"	57/8"	81/4"	81/4"	81/4*	81/4"
d		1/2"	1/2"	1"	1"	1"	11/2"	$1^{1/2^{*}}$	13/4"	13/4"	17/8"	17/8"
F	FL	5"	5"	5"	6"	8"	8"	8"	8"	8"	8"	8"
E	MJ	81/2"	81/2*	81/2"	8 5/8"	91/4*	91/4"	111/2"	11 7/8"	121/4*	121/2"	131/4*

Larger Sizes Available. Design and Materials Subject to Change Without Notice. Call for Verification and Any Updated Drawings