

# SERIES 3000 - AWWA C500

SIZES: 2" - 108"

TYPE: OUTSIDE SCREW & YOKE (OS&Y)

## FULL NOMINAL PIPE SIZE PORT AREA SIZES: 54" & LARGER

### BODY

Ductile Iron with Low-Zinc  
Bronze Seat Ring

### WEDGE

Ductile Iron with Low-Zinc  
Bronze Seat Ring

### STEM

Stainless Steel  
(Other Materials Available)

### STEM NUT

Low-Zinc Aluminum Bronze

### SEAT RINGS

Low-Zinc Bronze

### COATING

ANSI/NSF-61: 2-Part  
Thermal Epoxy  
(Inside and Outside per AWWA C550)

### ROLLERS, TRACKS, & SCRAPER

30" & Larger - RTS on Both  
Sides of Body for Vertical or  
Horizontal Installation

### BONNET

Ductile Iron

### NUTS, BOLTS, WASHERS

Stainless Steel

### BY-PASS

Integral By-pass, Available  
(sized per AWWA C500 Standard)

### END-CONNECTIONS

Flange up to 108" or  
Mechanical Joint up to 48"

### TYPES

Non-Rising Stem (NRS) or  
Outside Screw and Yoke (OS&Y)



Design and Materials Subject to Change Without Notice. Call for Verification and Any Updated Drawings